



**HYPER POOL GROUP**



### **POOL GUARD POOL PAINT – APPLICATION GUIDELINES.**

#### **Notes on PREPARATION**

• *In case of water seepage due to cracks in the structure or surface, HPG has a range of products available for this. Please enquire with your relevant branch.*

#### **IMPORTANT INFO**

- Do not cover the pool during the curing period after the 2nd coat.
- Once re-filled avoid sprinkling granular chlorine directly into the water, rather add chlorine via the weir to pass through the sand filter.
- All pool paints will eventually fade in colour when exposed to the chemical dosing of water. Prolonged colour fastness can be achieved with regularly maintaining the correct water balance.
- PoolGuard Pool Paint should not be used in hot tubs and spas, due to high water temperatures.
- Use of Platinum Pool Paint on surfaces not mentioned herein is not recommended.
- Avoid thick layering of 1st or 2nd coats to prevent blistering / immersion.
- Over-application will extend both the minimum overcoating periods and handling times and may be detrimental to the long-term overcoating properties.

#### **DISCLAIMER**

Overcoating information is given for guidance only and is subject to local and environmental conditions.

Consult with a representative for specific recommendations. Test performance results were obtained in a controlled environment and makes no claim that the exhibited / published results or any other tests accurately represents results that may be found in any of the various field environments. Application, environmental, existing surface condition, and or weathering and design factors can vary across sites. Due care should therefore be exercised in the selection, performance verification and use of the coating. Store between 5°C and 35°C.